

Package: HTGM3D (via r-universe)

May 26, 2026

Version 1.0.3

Date 2026-04-26

Title Three Dimensional High Throughput 'GoMiner'

Maintainer Barry Zeeberg <barryz2013@gmail.com>

Author Barry Zeeberg [aut, cre]

Depends R (>= 4.2.0)

Imports minimalistGODB, GoMiner, HTGM, HTGM2D, grDevices, stats,
R2HTML, rgl, vprint, randomGODB, stringr, salesforcer

LazyData true

LazyDataCompression xz

Description The Gene Ontology (GO) Consortium
<<https://geneontology.org/>> organizes genes into hierarchical
categories based on biological process (BP), molecular function
(MF) and cellular component (CC, i.e., subcellular
localization). Tools such as 'GoMiner' (see Zeeberg, B.R.,
Feng, W., Wang, G. et al. (2003) <[doi:10.1186/gb-2003-4-4-r28](https://doi.org/10.1186/gb-2003-4-4-r28)>)
can leverage GO to perform ontological analysis of microarray
and proteomics studies, typically generating a list of
significant functional categories. To capture the benefit of
all three ontologies, I developed 'HTGM3D', a three-dimensional
version of 'GoMiner'.

License GPL (>= 2)

Encoding UTF-8

VignetteBuilder knitr

Suggests knitr, rmarkdown, testthat (>= 3.0.0)

RoxygenNote 7.3.3

Config/testthat/edition 3

NeedsCompilation no

Config/pak/sysreqs cmake libfreetype6-dev libglu1-mesa-dev make texlive libicu-dev libpng-
dev libuv1-dev libxml2-dev libgl1-mesa-dev libssl-dev libx11-dev zlib1g-dev

Repository <https://barryzee.r-universe.dev>

Date/Publication 2026-04-26 19:15:59 UTC

RemoteUrl <https://github.com/cran/HTGM3D>

RemoteRef HEAD

RemoteSha fb7eab79fa61c3b366fd166442f835152d151027

Contents

blackBodyRadiationColors	2
catNum3	3
cluster52	4
graphIt	4
Housekeeping_Genes	4
HTGM3D	5
HTGM3Ddriver	6
insertCatSize	7
interactWithGraph3D	8
Jaccard3	8
plot3Dmat	9
pruneCatGenes	10
showGenes	10
subMatDiffs	11
whichOS	12
x_cg	12
x_l	12
x_m11	13
x_mat	13
x_mat3d	13
Index	14

blackBodyRadiationColors

blackBodyRadiationColors

Description

set up color scale for black body spectrum

Usage

```
blackBodyRadiationColors(x, max_value = 1)
```

Arguments

x	numeric should be between 0 (black) and 1 (white)
max_value	numeric maximum value to be used for scaling

Details

I obtained this by copy and paste from internet (reference unknown)

Value

returns no value, but has side effect of generating color map

Examples

```
colors.blackBody <- rev(blackBodyRadiationColors(seq(0.3,1,length.out=20)))
```

 catNum3

catNum3

Description

assign the axis coordinate number to be used for the plotting position for each category

Usage

```
catNum3(1)
```

Arguments

1 list each component corresponds to an ontology branch, and contains the decreasing sorted tabulation of output of the number of times that a category appears in a triplet

Details

a component of 1 is like: GO_0005515__protein_binding GO_0042802__identical_protein_binding
GO_0005178__integrin_binding 38 4 3

a component of 11 is like: GO_0005515__protein_binding GO_0042802__identical_protein_binding
GO_0005178__integrin_binding 1 2 3

Value

returns a list each component corresponds to an ontology branch, and contains a vector of category plotting positions

Examples

```
#load("data/x_1.RData")
catNum3(x_1)
```

cluster52	<i>HTGM3D data set</i>
-----------	------------------------

Description

HTGM3D data set

Usage

data(cluster52)

graphIt	<i>graphIt</i>
---------	----------------

Description

annotate a selected point in the 3d graphic

Usage

graphIt(mat3d, sp, w, r, verbose)

Arguments

mat3d	component of HTGM3Ddriver() output list
sp	integer vector containing c(x,y,z) coordinated of point
w	integer line number within mat3d
r	numeric max value of x,y,z ranges
verbose	integer vector representing vprint classes

Value

returns no value, but has side effect of annotating the 3D graph

Housekeeping_Genes	<i>HTGM3D data set</i>
--------------------	------------------------

Description

HTGM3D data set

Usage

data(Housekeeping_Genes)

HTGM3D

HTGM3D

Description

compute matrix to use as input to plot3d()

Usage

```
HTGM3D(dir, geneList, GOGO3, thresh1, thresh3, mn, mx, pcgMN, pcgMX, verbose)
```

Arguments

<code>dir</code>	character string full path name to the directory acting as result repository
<code>geneList</code>	character vector of user-supplied genes of interest
<code>GOGO3</code>	return value of subsetGOGO3()
<code>thresh1</code>	numerical acceptance threshold for individual ontologies
<code>thresh3</code>	numerical acceptance threshold for joint ontology
<code>mn</code>	integer min category size threshold passed to trimGOGO3()
<code>mx</code>	integer max category size threshold passed to trimGOGO3()
<code>pcgMN</code>	integer param passed to pruneCatGenes
<code>pcgMX</code>	integer param passed to pruneCatGenes
<code>verbose</code>	integer vector representing vprint classes

Value

returns matrix containing information that provides the input needed for running plot3d()

Examples

```
## Not run:
# GOGO3.RData is too large to include in the R package
# so I need to load it from a file that is not in the package.
# Since this is in a file in my own file system, I could not
# include this as a regular example in the package.
# you can generate it using the package 'minimalistGODB'
# or you can retrieve it from https://github.com/barryzee/GO/tree/main/databases
load("/Users/barryzeeberg/personal/GODB_RDATA/goa_human/GOGO3_goa_human.RData")

geneList<-cluster52
dir<-tempdir()
mat3d<-HTGM3D(dir,geneList,GOGO3,thresh1=3,thresh3=3,mn=2,
  mx=10000,pcgMN=2,pcgMX=200,verbose=1:5)

## End(Not run)
```

HTGM3Ddriver

HTGM3Ddriver

Description

driver to invoke HTGM3D()

Usage

```
HTGM3Ddriver(
  dir,
  geneList,
  GOGO3,
  thresh1,
  thresh3,
  mn,
  mx,
  pcgMN,
  pcgMX,
  verbose
)
```

Arguments

<code>dir</code>	character string full path name to the directory acting as result repository
<code>geneList</code>	character vector of user-supplied genes of interest
<code>GOGO3</code>	return value of <code>subsetGOGO3()</code>
<code>thresh1</code>	numerical acceptance threshold for individual ontologies
<code>thresh3</code>	numerical acceptance threshold for joint ontology
<code>mn</code>	integer min category size threshold passed to <code>trimGOGO3()</code>
<code>mx</code>	integer max category size threshold passed to <code>trimGOGO3()</code>
<code>pcgMN</code>	integer param passed to <code>pruneCatGenes</code>
<code>pcgMX</code>	integer param passed to <code>pruneCatGenes</code>
<code>verbose</code>	integer vector representing <code>vprint</code> classes

Details

suggested standardized class codes for `vprint()` -1 = developer debugging only 0 = constitutively turned on 1 = help for new user 2 = follow progress of long computation 3 = primary results 4 = meta information (e.g. dims of a matrix before and after trimming) 5 = warnings 6 = errors

Value

returns matrix containing information that provides the input needed for running `plot3d()`

Examples

```
## Not run:
# GOGOA3.RData is too large to include in the R package
# so I need to load it from a file that is not in the package.
# Since this is in a file in my own file system, I could not
# include this as a regular example in the package.
# you can generate it using the package 'minimalistGODB'
# or you can retrieve it from https://github.com/barryzee/GO/tree/main/databases
load("/Users/barryzeeberg/personal/GODB_RDATA/goa_human/GOGOA3_goa_human.RData")

geneList<-cluster52
dir<-tempdir()
l3<-HTGM3Ddriver(dir,geneList,GOGOA3,thresh1=3,thresh3=3,
  mn=2,mx=20000,pcgMN=2,pcgMX=200,verbose=1:5)

## End(Not run)
```

insertCatSize

insertCatSize

Description

compute fraction of total genes in the entire ontology that map to each category, and insert column into matrix mat

Usage

```
insertCatSize(mat, GOGOA3)
```

Arguments

mat	return value of Jaccard3()
GOGOA3	return value of subsetGOGOA()

Value

returns augmented version of matrix mat

Examples

```
## Not run:
# GOGOA3.RData is too large to include in the R package
# so I need to load it from a file that is not in the package.
# Since this is in a file in my own file system, I could not
# include this as a regular example in the package.
# you can generate it using the package 'minimalistGODB'
# or you can retrieve it from https://github.com/barryzee/GO/tree/main/databases
load("/Users/barryzeeberg/personal/GODB_RDATA/goa_human/GOGOA3_goa_human.RData")
```

```
mat2<-insertCatSize(x_mat,GOG0A3)

## End(Not run)
```

interactWithGraph3D *interactWithGraph3D*

Description

rotate the 3d graph and/or select a point within the 3D graph, and annotate that point

Usage

```
interactWithGraph3D(mat3d, maxfract = 1, newWindow = TRUE, verbose = TRUE)
```

Arguments

mat3d	component of HTGM3Ddriver() output list
maxfract	numeric upper threshold for category size to display
newWindow	Boolean if TRUE open new window to avoid over writing current window
verbose	integer vector representing vprint classes

Value

returns -1 if OS is OSX 26.2 which has glitch with rgl package

Examples

```
if(interactive()){
  interactWithGraph3D(x_mat3d)
}
```

Jaccard3

Jaccard3

Description

compute the number of genes in the intersection of categories from 3 ontology branches

Usage

```
Jaccard3(dir, m, thresh1 = 3, thresh3 = 3, verbose = 2)
```

Arguments

dir	character string full path name to the directory acting as result repository
m	return value of pruneCatGenes()
thresh1	parameter passed to Jaccard3()
thresh3	parameter passed to Jaccard3()
verbose	integer vector representing vprint classes

Value

returns matrix tabulating genes in the intersection of categories from 3 ontology branches also has side effect of saving files containing those genes

Examples

```
#load("data/x_m11.RData")
Jaccard3(tempdir(), x_m11, thresh1=3, thresh3=3, verbose=1:5)
```

plot3Dmat

plot3Dmat

Description

compute x,y,z coordinates for each triplet

Usage

```
plot3Dmat(mat, l)
```

Arguments

mat	return value of HTGM3D()
l	return value of catNum3()

Value

augmented version of matrix containing x,y,z coordinates for each triplet

Examples

```
#load("data/x_mat.RData")
#load("data/x_l.RData")
p3<-plot3Dmat(x_mat, x_l)
```

pruneCatGenes	<i>pruneCatGenes</i>
---------------	----------------------

Description

eliminate those categories to which no genes map

Usage

```
pruneCatGenes(m, mn = 2, mx = 200)
```

Arguments

m	the return value of catGenes()
mn	integer min category size threshold passed to trimGOGOA3()
mx	integer max category size threshold passed to trimGOGOA3()

Value

returns pruned version of matrix m

Examples

```
#load("data/x_cg.RData")
m<-pruneCatGenes(x_cg,2,200)
```

showGenes	<i>showGenes</i>
-----------	------------------

Description

open gene list in a textEdit window

Usage

```
showGenes(mat3d, w, range, npad)
```

Arguments

mat3d	component of HTGM3Ddriver() output list
w	integer line number within mat3d
range	list of ranges
npad	integer number of blanks for padding

Value

returns no value, but has side effect of opening textEdit

`subMatDiffs`*subMatDiffs*

Description

retrieve submatrices of common rownames and colnames, and report differences

Usage

```
subMatDiffs(m1, m2, verbose = 3)
```

Arguments

<code>m1</code>	matrix
<code>m2</code>	matrix
<code>verbose</code>	integer vector representing vprint classes

Details

compare submatrices of `m1` and `m2` that have common rownames and colnames

Value

returns no values

Examples

```
rn<-c("a", "b", "c")
cn<-c("a", "b", "c", "d")
m1<-matrix(1:12, nrow=length(rn), ncol=length(cn))
rownames(m1)<-rn
colnames(m1)<-cn
m2<-m1
subMatDiffs(m1, m2)

m3<-m1
m3[1, 1]<-0
m3[1, 2]<-0
subMatDiffs(m1, m3)

m4<-m3
colnames(m4)<-c("aa", "b", "c", "d")
subMatDiffs(m1, m4)
```

whichOS	<i>whichOS</i>
---------	----------------

Description

determine if host machine is running OSX Tahoe 26.2

Usage

whichOS()

Details

as of Feb 6 2026 Tahoe 26.2 does not interact properly with rgl Xwindows package

Value

"BAD" Tahoe 26.2 or later, "OK" otherwise

x_cg	<i>HTGM3D data set</i>
------	------------------------

Description

HTGM3D data set

Usage

data(x_cg)

x_1	<i>HTGM3D data set</i>
-----	------------------------

Description

HTGM3D data set

Usage

data(x_1)

x_m11	<i>HTGM3D data set</i>
-------	------------------------

Description

HTGM3D data set

Usage

data(x_m11)

x_mat	<i>HTGM3D data set</i>
-------	------------------------

Description

HTGM3D

Usage

data(x_mat)

x_mat3d	<i>HTGM3D data set</i>
---------	------------------------

Description

HTGM3D

Usage

data(x_mat3d)

Index

`blackBodyRadiationColors`, [2](#)

`catNum3`, [3](#)

`cluster52`, [4](#)

`graphIt`, [4](#)

`Housekeeping_Genes`, [4](#)

`HTGM3D`, [5](#)

`HTGM3Ddriver`, [6](#)

`insertCatSize`, [7](#)

`interactWithGraph3D`, [8](#)

`Jaccard3`, [8](#)

`plot3Dmat`, [9](#)

`pruneCatGenes`, [10](#)

`showGenes`, [10](#)

`subMatDiffs`, [11](#)

`whichOS`, [12](#)

`x_cg`, [12](#)

`x_l`, [12](#)

`x_m11`, [13](#)

`x_mat`, [13](#)

`x_mat3d`, [13](#)